Refrigeration **SKB1200NS-A Series** Project: ActiveCore Series, 2 Door (Solid), Upright Fridge Item No: 1280 50 ľ 745 390 595 Solid swing door 745 50 Hinde Rear stand-off 0 **Optional LED** interior lighting Recessed door handles 930 2005* 50mm retractable rear stand-off SKOPE-connect[™] compatible controller Power cord 65 Floor clearance 4 × 100mm high swivel castors (front lockable) (Ø70 wheel) CABINET Doors 2 × lockable, self-closing, foamed, solid swing doors (hinged LH, RH) 2 × door openings: 1454mm high × 525mm wide Internal door opening 8 × wire and 2 × stainless steel Shelves Wire shelves: Adjustable height, 577mm wide × 520mm deep Stainless steel bottom shelf: Not adjustable, 580mm wide × 515mm deep Sign n.a. Material Powdercoat galvanized steel or stainless steel interior & exterior DIMENSIONS PERFORMANCE Internal External Max. ambient temp. 40°C Height 2005mm* 1454mm Temperature range 1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C) Width 1280mm 1180mm **GEMS** class 5M1 Depth 795mm 602mm GEMS energy consumption 2.93 kWh/24h 1.08m² Floor area 321 p.a.(@ \$0.30/kWh) GEMS annual running cost Weight 245kg ELECTRICAL Volume 1079L 801L Electrical safety climate class 5 Net volume *Height 2005mm includes top door hinges No interior lights or with interior lights: 2 × 1370mm, 15W LED Interior side lighting Interior shelf lighting n.a. Dimensional tolerances Sign lighting n.a. Before installing this cabinet allow the following Power cord Supplied with 2.0m, 10 Amp plug and lead dimensional tolerances Linear dimensions Overall cabinet dimensions Power supply 220-240 Volts a.c. 50 Hz, single phase supply Less than 1 metre ±5mm 3.0 Amps (includes unit 2.6 Amps) Current draw -5mm to +10mm More than 1 metre REFRIGERATION Length of multiple cabinets At each end wall At each joint Controller SCS Connect (SKOPE-connect[™] compatible) Less than 1 metre +5mm +15mm Connectivity interface Bluetooth More than 1 metre -5mm to +10mm +15mm Bottom mounted, integral, removable ActiveCore refrigeration unit Refrigeration system (UBHCNI-0008) Ventilation requirements R290 / 99g (natural refrigerant) Тор 50mm Refrigerant Sides Not required Nominal capacity 740 Watts Back 50mm Heat rejection (Avg/peak) 120 Watts/150 Watts Bottom 50mm Drainage No plumbing required PSS0580 Rev. 2.1 Mar. 202 SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2019 SKOPE Industries Limited



specifications