


specifications

CL600r-3SW

SKOPE Counterline
3 Swing Door Remote Chiller(JD3203V)




CABINET DIMENSIONS

| | External | Internal |
|--------------------|--------------------|----------|
| Height: | 725mm* | 545mm |
| Width: | 2065mm | 1730mm |
| Depth: | 680mm** | 565mm |
| Floor area: | 1.40m ² | |

* Height excludes castors, legs or optional worktop

**Depth with optional worktop is 700mm



Copyright © 2003 SKOPE Industries Limited

CABINET SPECIFICATIONS

| | |
|------------------------------------|---|
| Refrigeration system: | Side mounted, remote refrigeration unit |
| Electronic controller: | SKOPE CAREL ir33 |
| Refrigerant: | Selected at time of order: R134a, R404A, R507, R22 |
| Pipe connection size: | Liquid line: 1/4". Suction line: 3/8" |
| Remote refrigeration duty: | 480 Watts |
| Cabinet internal volume: | 600 litres |
| Insulation: | 42mm polyurethane foam |
| Cabinet temperature range: | +1°C to +4°C in 40°C ambient |
| Drainage: | Small drain supplied. Must be connected to permanent drain by installer. |
| Electrical: | 230-240 Volts a.c. 50 Hz, single phase supply, 0.7 Amps |
| Internal lighting: | 1 x 24W T8 Frosted LED Tube (Ø26 x 1500mm, 5500K) - Switched |
| Internal door opening size: | 3 door openings: 544mm high x 520mm wide |
| Doors: | Self-closing, double glazed, toughened Low-E safety glass with aluminium extrusion or insulated solid doors |
| Worktop (optional): | Optional 20mm high stainless steel worktop with 65mm (or 50mm) fascia |
| Shelves: | Adjustable height, white plastic coated, steel wire shelves - two per door |

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0161 Rev. 4.1 Apr. 2016



SKOPE INDUSTRIES LIMITED



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.co.nz