

specifications


CC500r-3SW

SKOPE Counterline - Slimline
3 Swing Door Remote Chiller (JS3203V)

CABINET DIMENSIONS

	External	Internal
Height:	725mm*	545mm
Width:	2065mm	1730mm
Depth:	600mm	485mm
Floor area:	1.23m ²	

* Height excludes castors or legs



Copyright © 2007 SKOPE Industries Limited

CABINET SPECIFICATIONS

Refrigeration system:	Side mounted, remote refrigeration unit
Electronic controller:	SKOPE CAREL ir33
Refrigerant:	Selected at time of order: R134a, R404A, R507, R22
Pipe connection size:	Liquid line: 1/4". Suction line: 3/8"
Remote refrigeration duty:	540 Watts
Cabinet internal volume:	517 litres
Insulation:	50mm polyurethane foam
Cabinet temperature range:	+1°C to +4°C in 40°C ambient
Drainage:	Small drain supplied. Must be connected to permanent drain by installer.
Electrical:	230-240 Volts a.c. 50 Hz, single phase supply, 0.7 Amps
Internal lighting:	1 x 24W T8 Frosted LED Tube (Ø26 x 1500mm, 5500K) - Switched
Internal door opening size:	3 door openings: 544mm high x 520mm wide
Doors:	Self-closing, double glazed, toughened Low-E safety glass with aluminium extrusion or insulated solid doors
Worktop (optional):	Optional 20mm high stainless steel worktop with 65mm fascia
Shelves:	Adjustable height, white plastic coated, steel wire shelves - two per door

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0070 Rev. 4.1 Apr. 2016



SKOPE INDUSTRIES LIMITED



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.com