

MISA SERIES

Premium Range

Standard Cool and Freezer Room

Italian designed, premium polyurethane modular cool and freezer rooms provide a superior energy efficient solution for busy establishments requiring food storage management.

Benefits

Quick and easy assembly
Ideal for high ambient temperatures
Suitable for almost any location
Adaptable to changing circumstances
Options to suit



Warranty
2 year protection*

*2 year parts & 1 year labour if installed by a SKOPE approved MISA installer



Specifications

MISA Series

Modular Cool or Freezer Room System



	MODEL	FOOTPRINT REFERENCE	EXTERNAL DIMENSIONS	DESCRIPTION		
			W x D x H (mm)	Internal volume (m³)	Panel (mm)	
Cool Rooms	M-1A20-C	1A	1350 x 1350 x 2150	3.07	60	2m H
	M-2A20-C	2A	1750 x 1350 x 2150	4.07	60	
	M-2B20-C	2B	1750 x 1750 x 2150	5.39	60	
	M-3B20-C	3B	2150 x 1750 x 2150	6.72	60	
	M-3C20-C	3C	2150 x 2150 x 2150	8.37	60	
	M-4B20-C	4B	2550 x 1750 x 2150	8.04	60	
	M-4C20-C	4C	2550 x 2150 x 2150	10.01	60	
	M-4D20-C	4D	2550 x 2550 x 2150	11.99	60	
	M-5D20-C	5D	2950 x 2550 x 2150	13.96	60	2.4m H
	M-1A24-C	1A	1350 x 1350 x 2550	3.68	60	
	M-2A24-C	2A	1750 x 1350 x 2550	4.87	60	
	M-2B24-C	2B	1750 x 1750 x 2550	6.46	60	
	M-3B24-C	3B	2150 x 1750 x 2550	8.04	60	
	M-3C24-C	3C	2150 x 2150 x 2550	10.01	60	
	M-4B24-C	4B	2550 x 1750 x 2550	9.62	60	
	M-4C24-C	4C	2550 x 2150 x 2550	11.99	60	
	M-4D24-C	4D	2550 x 2550 x 2550	14.35	60	
	M-5D24-C	5D	2950 x 2550 x 2550	16.71	60	
<ul style="list-style-type: none">• 60mm high density polyurethane panel• MISA P250 insulated and reinforced galvanised steel roll in floor system with anti-slip coating• It is recommended that all single phase units are to be on a 20A circuit						
Freezer Rooms	M-2A20-F	2A	1830 x 1430 x 2230	4.07	100	2m H
	M-2B20-F	2B	1830 x 1830 x 2230	5.39	100	
	M-3B20-F	3B	2230 x 1830 x 2230	6.72	100	
	M-3C20-F	3C	2230 x 2230 x 2230	8.37	100	
	M-2A24-F	2A	1830 x 1430 x 2630	4.87	100	2.4m H
	M-2B24-F	2B	1830 x 1830 x 2630	6.46	100	
	M-3B24-F	3B	2230 x 1830 x 2630	8.04	100	
	M-3C24-F	3C	2230 x 2230 x 2630	10.01	100	
	<ul style="list-style-type: none">• 100mm thickness allows flexibility in either Cool or Freezer room size• MISA's patented "fast fit" twin hook CAMLOCK system requires no sealants, so rooms can be easily assembled and disassembled• Please contact your local SKOPE representative for full details					

MISA Freeblock

SKOPE recommend MISA Heavy Duty Freeblocks in any of the following circumstances:

- Door openings exceed 6/hr over any 4hr period
- Ambient temperature exceeds 32° C
- More than 10% of the total product mass needs to be pulled down to temperature (from ambient to chilled) in a 12 hour period
- Daily product handling greater than 30-35 kg/m³

MISA Standard Freeblock is recommended in the following circumstances:

- Door openings less than 6/hr over any 4hr period a day
- Ambient temperature up to 32° C
- Daily product handling 30-35 kg/m³

For information detailing power supply requirements please refer to our MISA Brochure

Email enquiry@skope.com
Freephone AUS 1800 121 535
Freephone NZ 0800 947 5673
Learn more at skope.com



HACCP Certified

MISA Commercial Cold Rooms are certified as food safe refrigeration units that are suitable for use in facilities that operate in accordance with a HACCP based Food Safety Programme

