


specifications

OD1100-2

SKOPE Open Deck Chiller (CAREL ir33)
Type: O11RP (High Sign)



Copyright © 2013 SKOPE Industries Limited

CABINET SPECIFICATIONS

Refrigeration system:	Bottom mount removable refrigeration unit with electronic controller (UB80AFD)
Electronic controller:	CAREL ir33 electronic controller
Refrigerant:	R404A / 1100g
Nominal compressor capacity:	2090 Watts
Cabinet internal volume:	1020 litres
Insulation:	50mm thick, high density cyclo-isopentane polyurethane foam
Operating temperature:	0°C to +5°C
Electrical:	230-240 Volts a.c. 50 Hz, Chiller: 5.8 Amps
Internal lighting:	1 x horizontal top light: 54W T5 fluorescent tube (Ø16mm x 1150mm)
Sign lighting:	1 x horizontal sign light: 54W T5 fluorescent tube (Ø16mm x 1150mm)
Power cord:	2.5m flexible power cord with 3-pin plug
Doors:	n.a.
Internal opening size:	1140mm wide x 1030mm high
Shelves:	4 x adjustable height, angled shelves (2 shelves 1150mm x 350mm and 2 shelves 1150mm x 390mm) and 1 x fixed in place, angled bottom tray (1150mm x 400mm).
Weight:	282 kg

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0304 Rev. 2.0 Mar. 2017



SKOPE INDUSTRIES LIMITED



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.co.nz