



# specifications

## PG250Prepr-2

SKOPE Gen2 Pegasus Horizontal 1/1  
REMOTE 2 Door Prep Chiller (JH8302)




### CABINET DIMENSIONS

|                    | External           | Internal |
|--------------------|--------------------|----------|
| <b>Height:</b>     | 751mm*             | 570mm    |
| <b>Width:</b>      | 1181mm             | 833mm    |
| <b>Depth:</b>      | 700mm              | 545mm    |
| <b>Floor area:</b> | 0.83m <sup>2</sup> |          |

\* Height excludes castors or legs.

Power Cord with 3-Pin Plug



Copyright © 2008 SKOPE Industries Limited

### CABINET SPECIFICATIONS

|                                    |  |
|------------------------------------|--|
| <b>Refrigeration system:</b>       | Electronic controlled, side mounted, remote refrigeration unit             |
| <b>Electronic controller:</b>      | CAREL ir33 electronic controller   |
| <b>Refrigerant:</b>                | Thermostatic expansion valve fitted as standard to suit R134a or R404A     |
| <b>Pipe connection size:</b>       | Liquid line: 1/4". Suction line: 3/8"                                      |
| <b>Remote refrigeration duty:</b>  | 500 Watts @ -10°C SST  |
| <b>Cabinet internal volume:</b>    | 260 litres   |
| <b>Insulation:</b>                 | 60mm thick, high density cyclo-isopentane polyurethane foam                |
| <b>Cabinet temperature range:</b>  | +1°C to +5°C up to 30°C ambient  |
| <b>Drainage:</b>                   | Evaporator drain fitted inside service compartment (requires plumbing)     |
| <b>Electrical:</b>                 | 230-240 Volts a.c. 50 Hz, 3.71 Amps  |
| <b>Internal lighting:</b>          | 1 x 5W T8 LED tube (Ø26 x 360mm) - Door activated                          |
| <b>Internal door opening size:</b> | 2 door openings: 570mm high x 365mm wide                                   |
| <b>Doors:</b>                      | Solid stainless steel, self-closing doors (with key lock) - LH & RH hinged |
| <b>Worktop:</b>                    | Worktop accepts 4 x 1/3 150mm deep pans or 8 x 1/6 150mm deep pans         |
| <b>Shelves:</b>                    | Two levels of non-tip, adjustable tray slides and/or shelves per door      |
| <b>Weight:</b>                     | 130 kg   |

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0190 Rev 4.1 Apr. 2016



**SKOPE INDUSTRIES LIMITED**



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.co.nz