COUNTER LINE SERIES

Standard Range

Display / Under Counter

Available in a range of depths, doors and installation heights, making this series ideal for restaurants, commercial kitchens and foodservice areas with non-gastronorm chiller requirements.

Options

R/H Services
S/S Countertop
Additional shelves
Door lock kit
Double Low/E Argon
Heated glass (swing door only)
Sliding doors

System overheat protection

Electronic controller with digital temperature display

Choice of two depths increases space-saving opportunities: Counterline series (CL) depth is 680mm, Slimline series (CC) depth is 600mm

Energy efficient, long-life LED lights and interior light switch

Available in white, black and stainless steel (additional cost applies on S/S)

CL400

SKOPE Cyclone™ refrigeration system

+1°C to +4°C in 40°C ambient (swing only), +1°C to +4°C in 32°C ambient (slide only)

Replaceable, long-life magnetic door gaskets

Adjustable legs (150 - 180mm) and swivel castors (115 - 180mm) for easy installation, positioning and relocation

Warranty
2 year protection

High Energy Efficiency

High Energy Efficiency models available

PSF0015

Specifications
Counterline Series
Display / Under Counter

Integral front elevation

Remote front elevation

CL400 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
CL400	127	Integral	Chiller
CL400r	112	Remote	Chiller

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	1600	1455	1120
Depth***	680	680	565

Gross Volume
390 litres
Total Shelf Area
1.74m² (including floor)
Floor Area
1.09m² (intergral)
0.99m² (remote)

- 12.75 MEPS (kWhr/24hr/m²)
- Remote refrigeration dut y 480 Watts at -5°C SST

CL400 2 DOOR

Integral front elevation

Remote front elevation

CL600 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
CL600	140	Integral	Chiller
CL600r	125	Remote	Chiller

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2210	2065	1730
Depth***	680	680	565

Gross Volume
600 litres
Total Shelf Area
2.70m² (including floor)
Floor Area
1.50m² (intergral)
1.40m² (remote)

- 11.65 MEPS (kWhr/24hr/m²)
- Remote refrigeration du ty 615 Watts at -5°C SST

CL600 3 DOOR

Integral front elevation

Remote front elevation

CL800 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
CL800	153	Integral	Chiller
CL800r	138	Remote	Chiller

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2820	2675	2340
Depth***	680	680	565

Gross Volume
810 litres
Total Shelf Area
3.66m² (including floor)
Floor Area
1.92m² (intergral)
1.80m² (remote)

- 8.74 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 850 Watts at -5°C SST

CL800 4 DOOR

Integral front elevation

Remote front elevation

CC300 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
CC300	122	Integral	Chiller
CC300r	107	Remote	Chiller

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	1600	1455	1120
Depth***	600	600	485

Gross Volume
335 litres
Total Shelf Area
1.48m² (including floor)
Floor Area
0.96m² (intergral)
0.87m² (remote)

- 11.65 MEPS (kWh/24hr/m²)
- Remote refrigeration dut y 400 Watts at -5°C SST

CC300 2 DOOR

Integral front elevation

Remote front elevation

CC500 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
CC500	135	Integral	Chiller
CC500r	120	Remote	Chiller

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2210	2065	1730
Depth***	600	600	485

Gross Volume
517 litres
Total Shelf Area
2.29m² (including floor)
Floor Area
1.33m² (intergral)
1.24m² (remote)

- 9.83 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 540 Watts at -5°C SST

CC500 3 DOOR

Integral front elevation

Remote front elevation

CC700 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
CC700	148	Integral	Chiller
CC700r	133	Remote	Chiller

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2820	2675	2340
Depth***	600	600	485

Gross Volume
700 litres
Total Shelf Area
3.11m² (including floor)
Floor Area
1.70m² (intergral)
1.60m² (remote)

- 9.75 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 660 Watts at -5°C SST

CC700 4 DOOR

***Height excludes castors (115 - 180mm) , legs (150 - 180mm) or optional countertop (20mm) **Smallest available internal height ***Depth excludes optional countertop (20mm)**

AUS 1800 121 535 / NZ 0800 947 5673. Copyright © SKOPE Industries Limited. All rights reserved. SKOPE Industries Ltd reserves the right to alter specifications without notice. Visit www.skope.com for the most recent specification documents.