# CENTAUR SERIES

## Standard Range

## Food Service / Under Counter

Designed with a heavy duty construction these chillers and freezers meet the demands of busy commercial kitchens and food service operations.

**Options**
Available in glass or solid doors (excluding BC070 & BC180-CS)

**Warranty**
2 year protection

PSF0009

# Specifications
## Centaur Series
## Food Service / Under Counter

Integral top view

Integral front elevation

### BC070 - SOLID DOOR

| Model | Weight (kg) | Integral/Remote | Chiller/Freezer |
|---|---|---|---|
| **BC070-CB-1R00S-E** | 78 | Integral | Chiller |

| | External (mm) | Internal (mm) |
|---|---|---|
| **Height*** | 860 | 560 |
| **Width** | 700 | 600 |
| **Depth**** | 725 | 530 |

**Gross Volume**
149 litres
**Floor Area**
0.51m²

- 2 adjustable shelves per door as standard
- 1°C to +4°C in 38°C ambient
- Minimum 150mm clear ventilation space required at the side and rear of the cabinet

**BC070**
1 DOOR

Integral top view

Integral front elevation

### BC120 - SOLID/GLASS DOORS

| Model | Weight (kg) | Integral/Remote | Chiller/Freezer |
|---|---|---|---|
| **BC120-C-2RROS-E** | 105 | Integral | Chiller |
| **BC120-C-2FFOS-E** | 105 | Integral | Freezer |
| **BC120-CG-2RROS-E (glass)** | 105 | Integral | Chiller |

| | External (mm) | Internal (mm) |
|---|---|---|
| **Height*** | 840 | 610 |
| **Width** | 1200 | 850 |
| **Depth**** | 725 | 530 |

**Gross Volume**
275 litres
**Floor Area**
0.87m²

- BC120-CG - 16.19 MEPS (kWh/24h/m²)
- 1 adjustable shelf per door as standard
- +1°C to +4°C in 38°C ambient (solid door chiller only)
- -18°C to -23°C in 38°C ambient (solid door freezer only)
- +1°C to +4°C in 32°C ambient (glass door chiller only)
- Minimum 150mm clear ventilation space required at the sides and rear of the cabinet

**BC120**
2 DOOR

Integral top view

Integral front elevation

### BC180 - SOLID/GLASS DOORS

| Model | Weight (kg) | Integral/Remote | Chiller/Freezer |
|---|---|---|---|
| **BC180-C-3RRRS-E** | 148 | Integral | Chiller |
| **BC180-CG-3RRRS-E (glass)** | 148 | Integral | Chiller |

| | External (mm) | Internal (mm) |
|---|---|---|
| **Height*** | 840 | 610 |
| **Width** | 1800 | 1450 |
| **Depth**** | 725 | 530 |

**Gross Volume**
469 litres
**Floor Area**
1.30m²

- BC180-CG - 14.38 MEPS (kWh/24h/m²)
- 1 adjustable shelf per door as standard
- +1°C to +4°C in 32°C ambient (glass door only)
- +1°C to +4°C in 38°C ambient (solid door only)
- Minimum 150mm clear ventilation space required at the sides and rear of the cabinet

**BC180**
3 DOOR

Integral top view

Integral front elevation

### BC180-CS - 6 DRAWER

| Model | Weight (kg) | Integral/Remote | Chiller/Freezer |
|---|---|---|---|
| **BC180-CS-6RROS-E** | 168 | Integral | Chiller |

| | External (mm) | Internal (mm) |
|---|---|---|
| **Height*** | 840 | 610 |
| **Width** | 1800 | 1450 |
| **Depth**** | 725 | 530 |

**Gross Volume**
469 litres
**Floor Area**
1.31m²

- 1°C to +4°C in 38°C ambient
- Pans/trays not included
- Minimum 150mm clear ventilation space required at the sides and rear of the cabinet

**BC180-CS**
6 DRAWER

***Height includes adjustable legs. Height 100mm - 160mm ** Depth includes 25mm spacer**

AUS 1800 121 535 / NZ 0800 947 5673. Copyright © SKOPE Industries Limited. All rights reserved. SKOPE Industries Ltd reserves the right to alter specifications without notice. Visit www.skope.com for the most recent specification documents.