

# specifications

## CL600-3SW


SKOPE Counterline  
3 Swing Door Integral Chiller (JD2203V)

### CABINET DIMENSIONS

	External	Internal
<b>Height:</b>	725mm*	545mm
<b>Width:</b>	2210mm	1730mm
<b>Depth:</b>	680mm**	565mm
<b>Floor area:</b>	1.50m <sup>2</sup>	

\* Height excludes castors, legs or optional worktop

\*\* Depth with optional worktop is 700mm



Copyright © 2003 SKOPE Industries Limited

### CABINET SPECIFICATIONS

<b>Refrigeration system:</b>	Side mounted, integral refrigeration unit (UE12AAC-173ZC)
<b>Electronic controller:</b>	SKOPE CAREL ir33
<b>Refrigerant:</b>	R134a / 425 g
<b>Nominal capacity:</b>	581 Watts
<b>Cabinet internal volume:</b>	600 litres
<b>Insulation:</b>	42mm polyurethane foam
<b>Cabinet temperature range:</b>	+1°C to +4°C in 40°C ambient
<b>Drainage:</b>	No plumbing required
<b>Electrical:</b>	230-240 Volts a.c. 50 Hz, single phase supply, 3.2 Amps
<b>Internal lighting:</b>	1 x 24W T8 Frosted LED Tube (Ø26 x 1500mm, 5500K) - Switched
<b>Internal door opening size:</b>	3 door openings: 544mm high x 520mm wide
<b>Doors:</b>	Self-closing, double glazed, toughened Low-E safety glass with aluminium extrusion or insulated solid doors
<b>Worktop (optional):</b>	Optional 20mm high stainless steel worktop with 65mm (or 50mm) fascia
<b>Shelves:</b>	Adjustable height, white plastic coated, steel wire shelves - two per door

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0158 Rev. 4.0 Mar. 2014



**SKOPE INDUSTRIES LIMITED**



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.co.nz