

specifications


CC700-4SW

SKOPE Counterline - Slimline
4 Swing Door Integral Chiller (JS2204V)

CABINET DIMENSIONS

| | External | Internal |
|--------------------|--------------------|----------|
| Height: | 725mm* | 545mm |
| Width: | 2820mm | 2340mm |
| Depth: | 600mm | 485mm |
| Floor area: | 1.70m ² | |

* Height excludes castors or legs



Copyright © 2007 SKOPE Industries Limited

CABINET SPECIFICATIONS

| | |
|------------------------------------|---|
| Refrigeration system: | Side mounted, integral refrigeration unit (UE21AAC-173ZC) |
| Electronic controller: | SKOPE CAREL ir33 |
| Refrigerant: | R134a / 425 g |
| Nominal capacity: | 737 Watts |
| Cabinet internal volume: | 700 litres |
| Insulation: | 50mm polyurethane foam |
| Cabinet temperature range: | +1°C to +4°C in 40°C ambient |
| Drainage: | No plumbing required |
| Electrical: | 230-240 Volts a.c. 50 Hz, single phase supply, 3.8 Amps |
| Internal lighting: | 2 x 20W T8 Frosted LED Tube (Ø26 x 900mm, 5500K) - Switched |
| Internal door opening size: | 4 door openings: 544mm high x 520mm wide |
| Doors: | Self-closing, double glazed, toughened Low-E safety glass with aluminium extrusion or insulated solid doors |
| Worktop (optional): | Optional 20mm high stainless steel worktop with 65mm fascia |
| Shelves: | Adjustable height, white plastic coated, steel wire shelves - two per door |

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0071 Rev. 4.0 Mar. 2014



SKOPE INDUSTRIES LIMITED



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.com