specifications

BME1500-A Series

Bottom Mount ActiveCore Three Door Upright Chiller

CABINET DIMENSIONS

	External	Internal
Height:	2005mm* / 2195mm**	1454mm
Width:	1640mm	1540mm
Depth:	795mm	602mm
Floor area:	1.34m^2 (includes door handle)	

* Height 2005mm without sign (model BME1500-A)
** Height 2195mm with sign (model BME1500-AC)
*** Depth 745mm excludes removable door handle, door lock bracket and rear stand-off.

Copyright © 2016 SKOPE Industries Limited

GENERAL SPECIFICATIONS

Temperature range	1°C to 4°C (adjustable up to 15°C)
Climate class	5 (Tested at 43°C)
Doors	Lockable, self-closing, reversible, double glazed, single Low-E, argon filled, toughened safety glass swing doors (hinged LH, LH, RH)
Internal Volume	1433 litres
Interior lighting	2 × 20W T8 LED tube (Ø26mm × 1350mm) side lights and 1 x 20W (1400mm) LED module strip pillar light
Shelves	12 adjustable height wire shelves: 490 wide × 520 deep (4 each side), 540 wide x 520 deep (4 middle) plus 3 stainless steel bottom shelves: 485 wide × 515 deep (side), 545 wide x 515 deep (middle)
Power supply	220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug
Current draw	4.8 Amps (includes unit 4.0 Amps)
Refrigeration system	Removable ActiveCore bottom mount refrigeration unit (UBHCCI-0003)
Refrigerant	R134a / 475g
Nominal capacity	1000 Watts
Controller	Carel S4 electronic controller
Drainage	No plumbing required
Weight	330 kg

INDIVIDUAL SPECIFICATIONS

Model	BME1500-A	BME1500-AC
Part number	SM15GV	SM15BV
Sign	No sign	200mm high illuminated sign
Sign lighting	n.a.	1 × 22W T8 LED tube (Ø26mm × 1500mm)

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0469 Rev. 2.0 Apr. 2017

SKOPE INDUSTRIES LIMITED
Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673
Email: skope@skope.co.nz, Website: www.skope.com