# specifications

# TME1000-A Series

Top Mount ActiveCore
Two Door Upright Chiller

## CABINET DIMENSIONS

| | External | Internal |
|---|---|---|
| **Height:** | 2200mm | 1570mm |
| **Width:** | 1130mm | 1030mm |
| **Depth:** | 745mm | 554mm |
| **Floor area:** | 0.84m$^2$ (includes door handle) | |

* Depth 695mm excludes removable door handle and door lock bracket.

Copyright © 2016 SKOPE Industries Limited

## GENERAL SPECIFICATIONS

| | |
|---|---|
| **Temperature range** | 1°C to 4°C (adjustable up to 15°C) |
| **Climate class** | 5 (Tested at 43°C) |
| **Doors** | Lockable, self-closing, reversible, double glazed, single Low-E, argon filled, toughened safety glass swing doors (hinged LH, RH) |
| **Internal Volume** | 980 litres |
| **Interior lighting** | 2 × 22W T8 LED tube (Ø26mm × 1500mm) side lights |
| **Shelves** | 10 adjustable height wire shelves: 500mm wide × 470mm deep (5 each door) |
| **Power supply** | 220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug |
| **Current draw** | 4.0 Amps (includes unit 2.9 Amps) |
| **Refrigeration system** | Removable ActiveCore top mount refrigeration unit (UTHCCI-0002) |
| **Refrigerant** | R134a / 380g |
| **Nominal capacity** | 836 Watts |
| **Controller** | Carel S4 electronic controller |
| **Drainage** | No plumbing required |
| **Weight** | 225 kg |

## INDIVIDUAL SPECIFICATIONS

| | | |
|---|---|---|
| **Model** | TME1000-A | TME1000-AC |
| **Part number** | SM10GV | SM10BV |
| **Sign** | Sign replacement panel | 400mm high illuminated sign |
| **Sign lighting** | n.a. | 1 × 17W T8 LED tube (Ø26mm × 1034mm) |

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0471 Rev.2.1 May 2017

SKOPE INDUSTRIES LIMITED
Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673
Email: skope@skope.co.nz, Website: www.skope.com