# specifications

# SKT500X

Top Mount
One Door Upright Chiller

## CABINET DIMENSIONS

| | External | Internal |
|---|---|---|
| **Height:** | 2200mm | 1570mm |
| **Width:** | 570mm | 470mm |
| **Depth:** | 745mm | 554mm |
| **Floor area:** | 0.43m$^2$ (includes door handle) | |

* Depth 695mm excludes removable door handle and door lock bracket.

Copyright © 2016 SKOPE Industries Limited

## GENERAL SPECIFICATIONS

| | |
|---|---|
| **Temperature range** | 1°C to 4°C (adjustable up to 15°C) |
| **Climate class** | 5 (Tested at 43°C) |
| **Door** | Lockable, self-closing, reversible, double glazed, single Low-E, argon filled, toughened safety glass swing door (hinged RH) |
| **Internal Volume** | 445 litres |
| **Shelves** | 5 adjustable height wire shelves: 447mm wide × 475mm deep |
| **Power supply** | 220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug |
| **Current draw** | 3.0 Amps (includes unit 1.8 Amps) |
| **Refrigeration system** | Removable top mount refrigeration unit (UT20APF) |
| **Refrigerant** | R134a / 370g |
| **Nominal capacity** | 581 Watts |
| **Controller** | Carel S4 electronic controller |
| **Drainage** | No plumbing required |
| **Weight** | 140 kg |

## INDIVIDUAL SPECIFICATIONS

| **Model** | SKT500X | SKT500X-C | SKT500X-CX |
|---|---|---|---|
| **Part number** | MT55GY | MT55BY | MT55BX |
| **Sign** | Sign replacement panel | 400mm high illuminated sign | |
| **Sign lighting** | n.a. | 1 × 5W T8 LED tube (Ø26mm × 360mm) | |
| **Interior side light** | 1 × 20W (1400mm) LED module strip RH side light (all models) | | |
| **Interior shelf lights** | n.a. | n.a. | 5 x 6W LED module strip shelf lights |

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0461 Rev.2.0 April 2017

SKOPE INDUSTRIES LIMITED
Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673
Email: skope@skope.co.nz, Website: www.skope.com