


# specifications

## SKB1200-A Series

### Bottom Mount ActiveCore Two Door Upright Chiller



Copyright © 2016 SKOPE Industries Limited

### GENERAL SPECIFICATIONS

Temperature range	1°C to 4°C (adjustable up to 15°C)
Climate class	5 (Tested at 43°C)
Doors	Lockable, self-closing, double glazed, single Low-E, argon filled, toughened safety glass swing doors (hinged LH, RH)
Internal Volume	1079 litres
Power supply	220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug
Current draw	4.5 Amps (includes unit 2.9 Amps)
Refrigeration system	Removable ActiveCore bottom mount refrigeration unit (UBHCCI-0001)
Refrigerant	R134a / 380g
Nominal capacity	836 Watts
Controller	Carel S4 electronic controller
Drainage	No plumbing required
Weight	245 kg

### INDIVIDUAL SPECIFICATIONS

Model	SKB1200-A	SKB1200-AC	SKB1200-ACX
Part number	MB12GY	MB12BY	MB12BX
Sign	n.a.	200mm high illuminated sign	
Sign lighting	n.a.	1 x 20W T8 LED tube (Ø26mm x 1200mm)	
Interior side lights	2 x 20W (1400mm) LED module strip side lights (all models)		
Interior shelf lights	n.a.	n.a.	10 x 8W LED module strip shelf lights
Shelves	8 x wire and 2 x stainless steel	10 x wire and 2 x stainless steel	10 x wire and 2 x stainless steel
	Wire shelves: Adjustable height, 577mm wide x 520mm deep		
	Stainless steel bottom shelf: Not adjustable, 580mm wide x 515mm deep		

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0466 Rev.3.0 Mar. 2018



**SKOPE INDUSTRIES LIMITED**

Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673

Email: skope@skope.co.nz, Website: www.skope.com

