


SKB900NT-A Series

ActiveCore Series, Tropical, 2 Door (Glass), Upright Fridge



Project:

Item No:



CABINET			
Model ID	SKB900NT-A	SKB900NT-AC	SKB900NT-ACX
Doors	2 × self-closing, double glazed, single Low-E, lockable, argon filled, toughened safety glass swing door (hinged LH, RH)		
Internal door opening	2 × door openings: 1454mm high × TBCmm wide		
Shelves	8 × wire and 2 × stainless steel	10 × wire and 2 × stainless steel	10 × wire and 2 × stainless steel
	Wire shelves: Adjustable height, 480mm wide × 520mm deep Stainless steel bottom shelf: Not adjustable, 485mm wide × 515mm deep		
Sign	n.a.	Illuminated sign	Illuminated sign
Material	Powdercoat galvanized steel or stainless steel interior & exterior		
PERFORMANCE			
Max. ambient temp.	40°C		
Temperature range	1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C)		
GEMS class	M2		
GEMS energy consumption	11.77 kWh/24h		
GEMS annual running cost	\$1,290 p.a. (@ \$0.30/kWh)		
ELECTRICAL			
Electrical safety climate class	7		
Interior side lighting	2 × 1370mm, 15W LED	2 × 1370mm, 15W LED	n.a.
Interior shelf lighting	n.a.	n.a.	10 × 415mm, 6W LED
Sign lighting	n.a.	1 × 1035mm, 12W LED	1 × 1035mm, 12W LED
Power cord	Supplied with 2.0m, 10 Amp plug and lead		
Power supply	220-240 Volts a.c. 50 Hz, single phase supply		
Current draw	4.5 Amps (includes unit 2.6 Amps)		
REFRIGERATION			
Controller	SCS Connect (SKOPE-connect™ compatible)		
Connectivity interface	Bluetooth		
Refrigeration system	Bottom mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-0008, 600 parameter set)		
Refrigerant	R290 / 99g (natural refrigerant)		
Nominal capacity	740 Watts		
Heat rejection (Avg/peak)	490 Watts/560 Watts		
Drainage	No plumbing required		

DIMENSIONS

Height	External 2005mm* / 2195mm**	Internal 1454mm
Width	1085mm	985mm
Depth	795mm	602mm
Floor area	0.86m ²	
Weight	220kg	
Gross volume	880L	

* Height 2005mm without sign (SKB900NT-A)

** Height 2195mm with sign (SKT900NT-AC/ACX)

*** Depth 745mm excludes removable door handle, door lock bracket and rear stand-off

Dimensional tolerances

Before installing this cabinet allow the following dimensional tolerances:

Linear dimensions		Overall cabinet dimensions	
Less than 1 metre		±5mm	
More than 1 metre		-5mm to +10mm	
Length of multiple cabinets			
		At each joint	At each end wall
Less than 1 metre		±5mm	+15mm
More than 1 metre		-5mm to +10mm	+15mm

Ventilation requirements

Ventilation requirements	
Top	50mm
Sides	Not required
Back	50mm
Bottom	50mm

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2019 SKOPE Industries Limited

SKOPE INDUSTRIES LIMITED

Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673

Email: skope@skope.com, Website: www.skope.com

PSS0603 Rev. 2.1 Aug. 2020

